



Technical Data sonnenBatterie pro 2.0

	2.0/22,5	2.0/30	2.0/37,5	2.0/45
Nominal battery capacity in kWh	22,5	30	37,5	45
Depth of discharge (DoD)	90 %			
Cell technology	LFP (Lithium Iron Phosphate)			
Weight in kg	131	154	177	200
Dimensions per unit (H/W/D) in cm	186/67/23 + 35 cm distance between units			
Nominal power (charging/discharging)	9.9 kW			
Max. inverter efficiency	96 %			
Max. battery efficiency	98 %			
Ambient temperature range	-5 °C – +45 °C ¹			
Dust & water protection	IP30			
Operating mode	three phase			
Tests and directives	VDE-AR-N 4105, Low Voltage Directive 2014/35/EU, EMC Directive 2014/30/EU, SGS TÜV Saar, IEC 62040-1, UN 38.3, IEC 62133, IEC 62619, IEC 62619, G83-2, G59-3, G100			
Battery service life	designed for 20 years			
Warranty	10 years ²			
Cycles	10,000 ²			
Charging time to 90 %, approx.	3 h	3.5 h	4 h	4.5 h

We reserve the right to make technical changes and updates without prior notice. Specific values, performance data and other information in this data sheet, brochures and other product information, as well as illustrations and drawings in these documents, are solely illustrative and are subject to ongoing revision and modification. We do not warrant the accuracy or completeness of any information in these documents unless otherwise explicitly stated. Only the information in order confirmation documents or purchase contracts is binding.

¹ Derating at approx. 35°C. ² Warranty on all parts. To learn more about our current warranty terms and conditions, please visit [sonnen.de/en/terms-and-conditions](https://www.sonnen.de/en/terms-and-conditions) or call our customer hotline and request a copy.